

THE LINN DIREKTOR

TECHNICAL SPECIFICATIONS

Type:	Knekt Line Receiver / Stereo Power Amplifier / Built-in RCU
Line level inputs:	Input impedance 9k Ω . Maximum input 5V rms
Tape output:	Output impedance 100 Ω . Output level = Line input level
Main system input:	Balanced audio and communications for connection only to a Knekt Line Driver or Intersekt
Audio Output:	Variable output with 60dB of gain control range. Maximum gain 12dB. Output impedance 100 Ω
Infrared outputs:	Constant current modulated drives. Drive level 6mA, carrier frequency range 30-60kHz, internally adjusted
Loudspeaker outputs:	Output power 25W 4 Ω , 20W 8 Ω , per channel
Mains input:	Switchable for 115V or 230V operation. 100V version available
Power consumption:	Idling 5W. Maximum input power 70W
Protection:	Fully protected against short circuit on loudspeaker outputs and over-heating. Automatic recover after protection shutdown.
Fuse Rating:	115V T800mA 230V T400mA
Mains input voltage:	115V setting: 104Vac to 126Vac. 50/60Hz 230V setting: 207Vac to 252Vac. 50/60Hz
RCU connector:	RJ 45 connector
Size:	80 mm (H) x 326 mm (W) x 320 mm (D)
Weight:	3.75 kg