



# LINN

## KEY FEATURES INCLUDE

- Five-way loudspeaker with four-way passive crossover
- Active Servo Bass System
- Two completely independent servo controlled bass drivers
- An ideal playback system for the Linn CD12 compact disc player and KLIMAX power amplifiers
- Supertweeter, tweeter and midrange domes are designed to minimise diffraction effects caused by horn mounting

The Komri is a new high performance loudspeaker which incorporates a number of highly innovative design features and sets new standards for high-performance monitoring.

Komri is a five-way loudspeaker which uses newly developed soft-dome technology for the mid-range, high frequency and very high frequency drivers. The upper drivers are mounted closely together in an optimized acoustic array, for uniform dispersion characteristics and a defined acoustic centre. The result is an exceptionally open and natural sound with an extremely stable sound stage.

The bass drive system incorporates new Linn Active Servo Bass technology, which incorporates the bass driver with the amplifier to minimize distortion. The bass response of the Komri is uniform to below 20Hz.

The first release of the Komri will be an upgradeable passive loudspeaker with an internal Active Servo Bass system. The four-way passive crossover uses the highest quality of air-cored, litz-wound inductors and polypropylene capacitors for minimum loss and distortion. The Active Servo Bass system is fed directly from the passive crossover for perfect matching. To allow for variations in the size and characteristics of listening rooms, the gain of the bass system can be adjusted via a control panel on the back of the loudspeaker. The passive version is upgradeable to a full active option.

## KOMRI

### SPECIFICATION

Linn's Flagship Five-way performance loudspeaker with four-way passive crossover



1



2



3

# KOMRI

## TECHNICAL SPECIFICATION

Linn's Flagship Five-way performance loudspeaker  
with four-way passive crossover

■	Introduced	2001
■	Type	Five-way loudspeaker
■	Frequency response	20Hz - 28kHz +/- 3dB
■	Efficiency	87dB/w at 1m
■	Nominal impedance	4 ohms
■	Width (including base)	420mm (16.6 inches)
■	Depth (including base)	520mm (20.5 inches)
■	Height (including base)	1163.5mm including spikes (45.8 inches)
■	Weight (including base)	80kg each (176lbs)

Linn Products Ltd  
Floors Road, Waterfoot, Glasgow G76 0EP, Scotland, UK.  
Telephone: +44 (0) 141 307 7777, Facsimile: +44 (0) 141 644 4262, Helpline: 0500 888909, E-mail: [helpline@linn.co.uk](mailto:helpline@linn.co.uk), Website: [www.linn.co.uk](http://www.linn.co.uk)

Linn Products Inc  
8787 Perimeter Park Boulevard, Jacksonville FL 32216, USA.  
Telephone: +1 (904) 645 5242, Facsimile: +1 (904) 645 7275, Helpline: 888-671-LINN, E-mail: [helpline@linninc.com](mailto:helpline@linninc.com), Website: [www.linninc.com](http://www.linninc.com)

Linn Deutschland GmbH  
Albert-Einstein-Ring 19, 22761 Hamburg, Deutschland.  
Telephone: +49-40-890 660-0, Facsimile: +49-40-890 660-29, E-mail: [info@linn-deutschland.com](mailto:info@linn-deutschland.com), Website: [www.linn.co.uk](http://www.linn.co.uk)

Linn Records Ltd  
257 Drakemire Drive, Castlemilk, Glasgow G45 9SZ, Scotland, UK.  
Telephone: +44 (0) 141 303 5027, Facsimile: +44 (0) 141 634 0733, Helpline/Mail order: +44 (0) 141 303 5029, E-mail: [records@linn.co.uk](mailto:records@linn.co.uk),  
Website: [www.linnrecords.com](http://www.linnrecords.com)