



Akubarik

Introduced	2013
Type	5-way floor-standing integrated active loudspeaker
Drive units	13 mm (0.5") dome 25 mm (1") dome 75 mm (3") dome 150 mm (6") upper bass 2 x 200 mm (8") isobaric lower bass
Operating volume	44 litres
Crossover options	Fully Aktiv (internal modules)
Crossover points	110 Hz, 318 Hz, 3.6 kHz, 9.84 kHz
Frequency range (-3dB)	28 Hz – 20+ kHz
Bass roll-on	19 Hz, 40 Hz, 60 Hz
Bass Shelf	0dB to -7dB in 1dB steps below 40Hz
Connection options	Balanced XLR
Input impedance	7.5k Ω
Amplifier Power	4x100W (4 Ω) + 1x 200W (4 Ω)
Magnetic shielding	No
Input Power (Sleep Mode)	3.5W
THD+N (amplifier stages @1kHz)	<0.002%
Power Amplifier Gain	22.6dB
Mains supply frequency	50-60 Hz
Mains input voltage (auto-sensing)	100-120 V 200-240 V
Weight (including stand)	46 kg / 101 lb
Dimensions (including stand)	1050 mm (H) x 351 mm (W) x 450 mm (D) 41.3 inches (H) x 13.8 inches (W) x 17.7 inches (D)
Dimensions (excluding stand)	246 mm (W) x 435 mm (D) 9.7 inches (W) x 17.1 inches (D)
Standard finishes	Black Ash, Cherry, Oak, Rosenut, Walnut , White
High gloss finishes	Piano Black, Cherry, Oak, Rosenut, Walnut , White, plus over 200 RAL Classic Gloss colours (all except luminous colours: RAL 3026, 3024, 2007, 2005 and 1026)