

LINN AV 5110 LOCAL LOUDSPEAKERS TOTAL FLEXIBILITY

The new **Linn AV 5110** Local Loudspeakers are stylish full-range high fidelity speakers packaged for maximum discretion and placement flexibility. Designed and engineered with the poise and precision required for a wide range of demanding applications, the **AV 5110s** are multi-purpose speakers suitable for demanding stereo Hi-Fi, or front, centre and rear channel use in A/V systems.

Offering exceptional all-round performance from a very compact package, **AV 5110** loudspeakers can fill a room with accurate full-range sound. Full magnetic screening enables placement of the AV 5110 alongside a TV without causing interference, and an aerodynamically shaped port provides outstanding efficiency and extended frequency response. The UV resistant cabinet can be painted making it suitable for Knekt applications where its compact dimensions enable discreet positioning and ease of installation for a wide range of domestic, professional, commercial and industrial applications.

The unique geometry of the **AV 5110** makes it suitable for use on a bookshelf, on a floor-stand or on the wall, mounted either vertically or horizontally. Water resistant construction means that it can be deployed all around a home - in the kitchen, lounge, bedroom, study, bathroom, garage, and so on - combining accuracy, discrete appearance and sonic poise.

For more information please contact Linn Products Ltd
Customer Services on Freephone 0500 888909

LINN AV 5110 LOCAL LOUDSPEAKER

TECHNICAL INFORMATION

- Type:** Small, full-range, multi-purpose, precision loudspeaker, 4 Ohm input impedance
- Function:** Two-way bass reflex for multi-purpose use. 3.2 litres. 60Hz-20kHz frequency response
- Applications:** Bookshelf, omni-directional wall bracket or floor stand mounting
- Construction:** Flame-retardant, UV stable, high-tech composite cabinet. Separate treble and bass enclosures
- Drive Units:** 1 x 10mm polymer dome treble, 1 x 80mm die-cast chassis bass
- Screening:** Full magnetic screening (<3 gauss)
- Efficiency:** 88dB/1W/1m
- Connectors:** Single pair, gold contact 4mm sockets and binding posts
- Dimensions:** Height 235mm, Width, 228mm, Depth 103mm, Weight 2.7kg
- Finishes:** Black, White (paintable)