



**The Independent Classik lights up life with Linn sound
The new alternative to the sound and looks of mass market
compact systems. Designed to be useful throughout a home -
in a kitchen, bedroom, living or student room - with Linn Classik
sound quality, it can even switch lighting on and off!**



SILVER

The Linn Classik is simple, stylish, fulfilling and fun to use. Connected to a pair of loudspeakers, the Classik forms an independent and versatile Linn complete entertainment system with all the advanced features needed to satisfy the most demanding hi-fi enthusiast or discriminating music lover.

Packed full of features and providing superb sound quality and remarkable value for money the Linn Classik combines high quality CD and radio sources, a most extensive flexible control system and very powerful stereo amplification in a single, discrete and compact package.

The Classik CD source uses Linn's high-accuracy pickup and decoding technology to deliver consistent audio performance and robust tracking ability. The tuner, with 80 station presets, accesses the AM and FM frequencies used throughout the world, and has an adjustable threshold control for the most refined performance on both strong and weak signals. The preamplifier section has two external line level audio inputs to connect additional audio sources, a tape monitoring facility and recording output and an external preamplifier output for additional power amplification when bi-amping. The high density stereo power amplifier in the Classik delivers 150 Watts into 4 Ohms, and has twin loudspeaker terminals to drive two pairs of loudspeakers simultaneously or to bi-wire a single pair. The Classik is simple to operate via the front control and display panel and from its remote handset.


User configurable functions in the Classik help to make it most easy and enjoyable to use. CLOCK, ALARM and TIMER features can pre-set the time of day or night when the unit can be programmed to switch on and shut-down automatically, and it can also operate external lighting, additional entertainment components or appliances for your convenience or security, via a 2-amp switched socket. Other user function options cover tuner, amplifier and CD operation and the DISPLAY Mode.



ATLANTIK GREEN



PACIFIK BLUE




ARTIK WHITE

CLASSIK by Linn

SIMPLE, ELEGANT, STYLISH, POWERFUL, FUN

The Linn Classik is supplied neat and complete with its headphone socket, AM and FM radio antennae, a 2.5 metre pair of plugged loudspeaker cables and a powerful remote control handset. Available in a choice of colours and together with matching 5110 loudspeakers, the Classik represents outstanding value for money. Linn market-leading sound quality is now even better value and, with a free five year warranty on offer, also more affordable. Available from Linn at Harrods, Linn specialists and other quality retailers world-wide.



The Linn Classik Technical Specifications

General

Dimensions: 80mm x 320mm x 325mm (H x W x D) Weight: 6kg

Power Consumption: 325W Maximum in normal operating mode. 25W typical use <3W in standby state

Main Supply Fuse: 100V T6.3Amp Anti-surge
115V T6.3Amp Anti-surge 230V T3.15Amp Anti-surge

Main Supply Tolerance: Nominal voltage $\pm 10\%$

Switched Output: 440W Maximum output.

CD Engine

Focus system

Triple Beam Laser Pickup

Conversion Technology

Delta Sigma

Tuner/Tuning Range

U.S.A. FM 87.5 - 108.5MHz
AM 530 - 1730kHz

Japan FM 75.5 - 108.5MHz
AM 530 - 1730kHz

Europe FM 87.5 - 108.5MHz
AM 522 - 1611kHz

Tuning Resolution

FM TUNE mode: 50kHz

FM SCAN mode: 100kHz

AM TUNE mode: 1kHz

AM SCAN mode: 10kHz U.S.A. & Japan 9kHz Europe

Presets

80 User definable presets

Signal Strength Meter: 0 to 50 scale

Mute/Scan Threshold

Adjustable in 50 steps: equal to the signal strengthmeter.

Preamplifier Inputs

Aux / Tape1 / Tape2, -10dBV (sensitivity)

10kW (load)

Preamplifier Outputs

Tape Output: equal to Aux. input level

Output impedance 100 Ohms

Pre-amp output: tracks volume +10dB

Output impedance 150 Ohms

Minimum load on outputs: 5k Ohms

Headphone

Output Impedance: < 8 Ohms

Output level: same as preamplifier output

Output Current Limit: 60mA

Load impedance: 8 Ohms - 2k Ohms

Power Amplifier

Voltage Gain 28.5dB

Power Output: 75W per Channel into 4 Ohms (nominal mains)

Finishes Black, Silver, Arctic White, Pacific Blue, Atlantik Green

