



Exakt Akubarik

Introduced	2014
Type	5-way floor-standing integrated active loudspeaker with Exakt Technology
Drive units	13 mm (0.5") silk dome 25 mm (1") dome tweeter 75 mm (3") dome midrange 150 mm (6") doped paper upper bass 2 x 200 mm (8") glass fibre composite isobarik lower bass
Operating volume	44 litres
Crossover options	Fully Aktiv Exakt (internal modules)
Crossover points	87 Hz, 360 Hz, 3.61 kHz, 8.87 kHz
Frequency range (-3dB)	28 Hz – 33 kHz
Connection options	Exakt Link
Amplifier Power	4x100W (4Ω) + 1x 200W (4Ω)
Magnetic shielding	Yes
Input Power (Sleep Mode)	<5mW
Input Power (Playback muted)	40W
Continuous Rated input	200W
Power Amplifier Gain	22.6dB
Mains supply frequency	50-60 Hz
Mains input voltage (auto-sensing)	100-120 V 200-240 V
Weight (including stand)	46.2 kg / 102 lb
Dimensions (including stand)	1050 mm (H) x 351 mm (W) x 450 mm (D) 41.3 inches (H) x 13.8 inches (W) x 17.7 inches (D)
Dimensions (excluding stand)	246 mm (W) x 435 mm (D) 9.7 inches (W) x 17.1 inches (D)
Standard finishes	Black Ash, Cherry, Oak, Rosenut, Walnut , White
High gloss finishes	Piano Black, Cherry, Oak, Rosenut, Walnut , White, plus over 200 RAL Classic Gloss colours (all except luminous colours: RAL 3026, 3024, 2007, 2005 and 1026)